



MATERIAL:
 Body: Nylon66, UL rated: 94V-2 min
 Actuator: Nylon66, UL rated: 94V-2 min
 Terminal: Brass, silver plated
 Rating: 2A 250V AC
 Function: ON-(OFF)-ON DT3P MOMENTARY
 Protection Grade: IP67
 Contact Resistance: 100mΩ Max
 Insulation Resistance: 100MΩ Min at DC 500V
 Dielectric Strength: 3000VAC 1 minute
 Electrical life: 50,000 cycles
 Mechanical life: 300,000 cycles
 Operating Temperature: -20°C~85°C
 Safety Approval: **RoHS**

SWITCHING CIRCUIT

DT3P MOMENTARY

	C1 NO1 NC1	C NO NC
	C1 NO1 NC1	C NO NC
	C1 NO1 NC1	C NO NC

东莞市创恩电子有限公司

公差 TOLERANCES	XX± 0.15	角度 ANGLE	±1°	单位	DIMENSION UNIT	mm.	
版本 VERSION	A0	比例尺 SCALE	1:1	日期 DATE	2024.06.19	品名 TITLE	图号 DRAWING NO
核准 APPROVED BY		核对 CHECKED BY		绘图 DRAWN BY		R	B
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.				XXXXXX